



Specifications



EUROLIGHT LD6230

Professional 6-Channel 10 A Dimmer Pack with DMX and Analog Control

EN EUROLIGHT LD6230**Professional 6-Channel 10 A Dimmer Pack with DMX and Analog Control**

- 6-channel, DMX/analog-controlled dimmer pack with up to 10 A load per channel
- 3-phase mains supply (one phase possible at lower output power)
- Standard DMX512 interface
- Additional 8-pin DIN connector for analog control (0 – 10 V)
- Adjustable Preheat and Limiter function to extend bulb life
- Precise “curve” function enables selection of different fade modes
- Switch option for simple on/off control of each channel
- Automatic digital input check to detect DMX signal errors
- Manual mode for dimming capability without an external lighting console
- Automatic store function saves all settings after leaving Configuration mode
- 3-digit display and dedicated control LEDs for better indication in dark environment
- Harting and CEE connection options (connectors not included)
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

Specifications**Channels**

Number	6
Load per channel	0.2 A min./10 A max.
Maximal load per channel	10 A using a 3-phase connector
Frequency	50/60 Hz

Inputs

Power supply	3-phase connector, internal terminal block/PG cable screw joint, CEE connector (optional installation by qualified professional)
Analog	0 to +10 V via 8-pin DIN
Digital	DMX512 via 5-pin XLR

Outputs

Digital	DMX512 via 5-pin XLR
Load	Internal terminal block/PG cable screw joint, HARTING (optional installation by qualified professional)

System Fuses

Load securing per channel	10 A cable protection switch (type C)
Control section fuse	2 x T 100 mA H/250 V (EU) 1 x T 160 mA H/250 V (EU) 2 x T 160 mA H/250 V (UL) 1 x T 315 mA H/250 V (UL)

Power Supply**Voltage**

USA/Canada	120 V~, 60 Hz
Europe/U.K./Australia	240 V~, 50 Hz
Maximum power consumption	3 x 20 A

Dimensions/Weight

Dimensions (H x W x D)	approx. 3 1/3 x 19 x 15 9/10" approx. 84.3 x 482.6 x 403.8 mm
Weight	approx. 21.6 lbs / 9.80 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HEREIN. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP AND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTAKING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC GROUP IP LTD. TRIDENT CHAMBERS, WICKHAMS CAY, P.O. BOX 146, ROAD TOWN, TORTOLA, BRITISH VIRGIN ISLANDS